



IA-60a 60W AC Adaptor

The IA-60a is a 60W AC adaptor with a single XLR output. The combination of reliable operation and a compact space saving design gives the IA-60a the competitive edge, especially when used on location or in the production studio. Even with its rugged metal enclosure the IA-60a weighs under 2 lbs., and its small size makes it easy to store for transport and use in a variety of applications.

The IA-60a is primarily used to power portable ENG cameras, but is also a proven power source for a wide range of camera lights, portable monitors and other broadcast equipment. It also offers complete peace of mind in terms of safety, with automatic overload protection just one of the safety features integral to the IA-60a.

IA-60a Product Features:

- **60W 13.8V DC output** via a 4-pin XLR connector.
- **The IA-60a weighs just 1.98 lbs.**, despite an all-purpose rugged metal enclosure. An integrated carry handle is provided for easy handling.
- **Internal safety features** protect the IA-60a from overload damage should an excessive load be drawn. It does this by automatically shutting down to recover. The IA-60a also produces 'low ripple noise' to reduce the chances of signal interference with nearby devices.
- **Adjustable output voltage** from 12.5V to 15V.
- **Universal AC input voltage** for worldwide operation.
- **Includes one CA4XLR 4-pin power supply connector cable** (10 ft.)

PROSeries



Technical Specification

Input:

AC 100~240V 50/60Hz

Power Consumption:

161VA max. (132VA:100V / 161VA:240V)

DC Output Capacity:

60W max., 13.8V
Adjustable: 12.5V-15V

DC Output Connector:

4-pin XLR connector
Pin 1: Negative
Pin 4: Positive

Dimensions:

3.54(W) x 1.97(H) x 7.48(D) inches

Weight:

1.98 lbs. approx.

